

EDELIVER 3 SPECIFICATIONS

| SPECIFICATIONS | MAXUS E DELIVER 3 | SWB 50.23KWH | CAB/CHASSIS 50.23KWH |
|--|---|-------------------|----------------------|
| ENGINE | WEIGHTS | | |
| eDeliver3 Standard Equipment | GVM (kg) | 2460 | 2535 |
| › 2 Driving Modes | CVW (kg) | 1555 | 1425 |
| › 3 Energy Recovery Modes | Max front axle load (kg) | 1170 | 1170 |
| › 6 Cargo Area Floor Strapping Rings | Max rear axle load (kg) | 1460 | 1460 |
| › Cargo Area Partition (Optional With Glass) | Payload (kg) | 905 | 1110 |
| › Daytime Running Lights | Max roof load (kg) | 75 | - |
| › Driver Airbag | Towing capacity (unbraked) (kg) | 500 | 500 |
| › Driver Seatbelt Lock Reminder | ENGINE | | |
| › Electric Adjustment Of Outside Mirror | Drive type | RHD | RHD |
| › Electric Power Assisted Steering | Number of seats | 2 | 2 |
| › Electric Windows | Rated power/Peak power (kW) | 90 | 90 |
| › ESC - Electronic Stability Control | Rated torque/Max. torque (Nm) | 255 | 255 |
| › Front & Rear Ventilated Discs | Max speed (kmph/mph) | 120/75 | 120/75 |
| › Front McPherson Independent Suspension | Acceleration 0-100km/h (sec) | 12 | 12 |
| › Front Passenger Airbag | GEAR RATIOS | | |
| › 7 inch Screen | Final Drive Ratios | | |
| › Handbrake | Max CVT | N/A | |
| › Immobiliser | 1 | 3.739 | |
| › Multifunction Steering Wheel | Min CVT | N/A | |
| › Rake Adjustable Steering Wheel | Reverse | 3.739 | |
| › Rear Leaf Spring Suspension | DIMENSIONS | | |
| › Reversing Camera | Dimension : LxWxH (mm) | 4555x1780x1895 | 5090x1780x1885 |
| › Rear Parking Sensors | Wheel base (mm) | 2910 | 3285 |
| › Stainless Steel Cargo Area Floor | Length cargo space (mm) | 2180 | - |
| › Ternary Polymer Lithium Battery | Max width cargo space (mm) | 1665 | - |
| | Max width cargo space between wheel arches (mm) | 1220 | - |
| | Max height cargo space (mm) | 1330 | - |
| | Slide door width (mm) | 710 | - |
| | Slide door height (mm) | 1230 | - |
| | Turning radius (m) | 5.87 | 5.87 |
| | Cargo volume (m³) | 4.8 | - |
| TRANSMISSION | CHARGING | | |
| | Charging time(AC 100%) h | 8 | 8 |
| | Charging time (DC 80%) min | 45 | 45 |
| | Battery capacity (kWh) | 50.23 | 50.23 |
| | Energy consumption WLTP combined (kWh/100km) | 23.63kWh/100km ** | 23.63kWh/100km** |
| | RANGE** | | |
| | WLTP City Range** | 344 KMS** | 344 KMS** |
| | WLTP Combined Range** | 243 KMS** | 243 KMS** |
| STEERING AND HANDLING | PAINT COLOURS | | |
| Electric power assisted steering | White - Standard Colour | | |
| COTECH suspension and steering tuning | Yellow Available at Extra Cost | | |
| Front suspension: McPherson Strut Assembly | Flame Red Available at Extra Cost | | |
| Rear suspension: Leaf Spring | Silver Available at Extra Cost | | |
| Wheel size: 15inch | Black Available at Extra Cost | | |
| Tyre size: 185/65R15 for 32.5kW Battery | NZ Post Blue Available at Extra Cost | | |
| Tyre size: 185/65R15C for 52kW Battery | | | |
| BRAKES | | | |
| Front brake size: 282mm Diameter Rotor | | | |
| Rear brake size: 271mm Diameter Rotor | | | |
| Anti-skid Braking System (ABS) | | | |
| Electronic brake force distribution (EBD) | | | |
| Brake assist system (BAS) | | | |



White - Standard Colour



Yellow Available at Extra Cost



Flame Red Available at Extra Cost



Silver Available at Extra Cost



Black Available at Extra Cost



NZ Post Blue Available at Extra Cost

Warranty - Bumper to Bumper 36 months or 100,000kms with Roadside Assist. Drivetrain/Battery Warranty 8 years/160,000kms.

LDV is part of SAIC, a Fortune Global 500 company, which sold over 6.5 million vehicles in 2016 making it the largest automotive manufacturer in China.

All information in this document is correct at time of publication however variations may occur from time to time and Great Lake Motor Distributors Limited insofar as is permitted by law to do so, shall not be liable in any way as a result of any reliance by any person on anything contained in this document.

****Range quoted is based on global WLTP test procedure carried out on a vehicle with a fully charged EV battery. Actual range may vary depending on external elements such as driving style, terrain, battery age, state of battery health and overall vehicle maintenance and condition.**